

DT8 ALL-PURPOSE DUCT TAPE

- Hand-tearability, high tensile strength and conformability
- Ideal for contoured surfaces and quick labelling
- Good tensile strength for light-duty bundling
- Use for poly abatement, quick repairs, splicing, temporary holding and fast attachments
- Aggressive, synthetic and natural rubber adhesive provides instant adhesion to a wide variety of surfaces, including metal, glass, plastic and sealed concrete
- Tightly woven scrim provides high tensile strength, which is ideal for bundling applications
- Width: 48 mm (2")
- Length: 55 m (180')
- Thickness: 8 mils



Priced per Roll

Model No.	Colour	Rolls /Case	Price /Each
PG118	Black	24	
PG116	Silver	24	

DT11 HEAVY-DUTY DUCT TAPE

- Hand-tearability, high tensile strength and conformability
- Moisture-resistant seal in many containment situations, such as pipe sealing and attaching heavy poly-draping
- Sticks immediately and stays on irregular, hard-to-bond surfaces without lifting
- Width: 48 mm (2")
- Length: 55 m (180')
- Thickness: 11 mils



Priced per Roll

Model No.	Colour	Rolls /Case	Price /Each
PG122	Black	24	
PG120	Silver	24	

DT17 SUPER-DUTY DUCT TAPE

- Ultra-thick, water-resistant backing resists wear and abrasion while still tearing easily by hand
- Superior strength for the most demanding applications
- Excellent for repairing, seaming, extra-strength bundling and helps in protecting metal parts and surfaces against sandblast overspray
- Aggressive rubber adhesive grips instantly to a wide variety of surfaces, including metal, glass, plastic and sealed concrete
- Tightly woven scrim provides high tensile strength, which is ideal for bundling applications
- Rolls stay cleaner with low-tack roll sides
- Width: 48 mm (2")
- Length: 32 m (105')
- Thickness: 17 mils



Priced per Roll

Model No.	Colour	Rolls /Case	Price /Each
PG124	Black	24	

ALUMINUM FOIL TAPE

- For general purpose use (seaming, patching and sealing)
- Acrylic adhesive has excellent adhesion and permanently bonds to clean/dry surfaces
- Ideal for HVAC applications
- Temperature Resistance: -20°C to 120°C




Priced per Roll

Model No.	Width	Length	Thickness mils	Price /Each
PG176	48 mm (1-7/8")	45.7 m (150')	1.5	
PG177	72 mm (3")	45.7 m (150')	1.5	
PG178	48 mm (1-7/8")	55 m (180')	2	
PG179	72 mm (3")	55 m (180')	2	
PG180	48 mm (1-7/8")	55 m (180')	4.8	

ALUMINUM FOIL TAPE

- For general purpose seaming, patching and sealing
- Acrylic adhesive has excellent adhesion to clean/dry surfaces
- Applications include HVAC duct wrap, protective mask for chemical stripping
- Temperature resistance: -37 °C to 176 °C



Priced per Roll

Model No.	Dimensions	Thickness Mils	Rolls /Case	Price /Each
PE553	48 mm x 54.8 m (2" x 180')	2	24	
PE554	72 mm x 54.8 m (3" x 180')	2	16	
PF307	48 mm x 45.7 m (2" x 150')	1.5	24	
PF308	72 mm x 45.7 m (3" x 150')	1.5	16	

PREMIUM BOPP FILM HVAC TAPE

- Acrylic based pressure-sensitive adhesive combined with the conformability/flexibility of biaxially oriented polypropylene (BOPP) film
- Provides superior sealing, protective benefits, and ease of handling
- Printed for easy identification/inspection and resistant to mold growth and high humidity
- Designed and engineered for use on Class 1 flexible duct for permanent seaming and sealing to enhance appearance and provide barrier protection
- All temperature rates, flame retardant, high shear, aggressive, and UV resistant
- Superior bonding at sub-zero or at elevated temperatures
- UV/temperature resistant acrylic adhesive combined with inorganic polypropylene film provides the longest lasting closure method
- Ideal for HVAC applications
- Intended for use on UL listed flexible duct (or other) meeting UL-181 standards
- Thickness: 3 mils
- Length: 109.9 m/360'



Priced per Roll

Model No.	Width	Colour	Rolls /Case	Price /Each
PF577	48 mm (2")	Black	24	
PF578	48 mm (2")	Metalized	24	