

HEAT STRESS METER/DATA LOGGER

- Measures indoor and outdoor WBGT (Wet Bulb Globe . Temperature), Black Globe (TG) temperature, humidity, wet bulb, dew point and air temperatures
- Adjustable audible WBGT alarm setting Real time data logger with integral •
- SD memory card (IC495 optional)
- Temperature is measured in °C or °F .

SPECIFICATIONS Indoor WBGT Range:

Outdoor WBGT Range: TG Temp. Range: Air Temp. Range: Humidity Range: Model No. IC502

Mfg. No. R6250SD Price/Each \$

0° to 59 °C 0° to 56 °C 0° to 80 °C 0° to 50 °C 5 % to 95 % RH





RECHARGEABLE INDOOR/ OUTDOOR FANS WITH USB PORT Includes a lithium-ion battery and charger cable Power indicator light equipped with 5 LED lights to indicate the battery gauge in every 20% Fan can be used in both indoor and outdoor conditions . Variable speed setting USB charging port on the control box can • be used to recharge digital devices The fan can pivot forwards to a range of 30°

HVAC

- and backwards to a range of 90°
- Colour: Yellow
- Voltage: 24 V •
- Power: 25 W RPM: 1700 •
- Re-Charge time: 4-5 Hrs

- .

	time at low speed: 24 Hrs time at high speed: 4 Hrs A				
Model			Price		
No.	Diameter"	CFM	/Each		
EA828	12	1600			

HEAVY-DUTY FIXED BELT DRIVE **DRUM FANS**

- Fully enclosed motor
- All-metal construction
- 12' power cord

MATRIX

186

1.91

						-
Model			No. of	CF	М	Price
No.	Diameter"	HP	Speeds	High	Low	/Each
EA662	42	3/4	2	20945	7400	

HIGH-VELOCITY OSCILLATING WALL FANS

- Adjustable tilting fan head
- Sliding switch at front of base
- Rotating or fixed air direction
- Voltage: 120 V

MATRIX


Model No.	Diameter"	HP	No. of Speeds	High	CFM Medium	Low	Price /Each
EA660	20	1/5	3	4800	4500	4000	

HIGH VELOCITY FLOOR FANS

- All-metal construction
- Vertical pivot fan head

MATRIX

Copper motor for longer lifetime



f Is	High	CFM Medium	Low	Prio /Eac		
	4800	4500	4000			



Mode No. of CFM /Each Diameter HP Speeds Hiał Medium Low EA661 1/5 4900 4400 4150 20 3

> ELECTRICAL & INSTRUMENTS