

CORDED SAWS

7 1/4" CIRCULAR SAWS W/HIGH STRENGTH BASE

- High strength base will withstand a one story drop
- 56° beveling capacity with stops at 45° and 22.5°
- Electric brake stops blade after use
- Includes: Carbide tipped blade, blade wrench and contractor bag

Model No. TSW598
Mfg. No. DWE575SB
Price/Each \$

SPECIFICATIONS

Amperage:	15.0
No Load RPM:	5200
Depth of Cut at 45°:	1 3/4"
Depth of Cut at 90°:	2 1/2"
Tool Weight:	8.8 lbs.



WORM DRIVE 7 1/4" CIRCULAR SAWS

- Lightweight magnesium and aluminum construction including durable magnesium foot plate
- Extra wide saw hook accepts materials up to 2-3/4"
- ToughCord™ cord protection system with cord jerk protection
- Electric brake stops the blade after trigger is released
- Accepts DWS5100 Dual Port Rip Guide (sold separately)
- Includes: Worm drive circular saw with grounded plug, 7-1/4" Carbide blade, Blade changing wrench

Model No. UA1800
Mfg. No. DWS535B
Price/Each \$

SPECIFICATIONS

Blade Diameter:	7-1/4"
No Load RPM:	4800
Amps:	15 A
Voltage:	120 V
Bevel Capacity:	53°
Bevel Stops:	22.5°, 45°



7 1/4" CIRCULAR SAWS

- High power, maximum cutting depth of 2 1/2"
- Electric brake, twin LED lights, heavy gauge aluminium base with ruler markings
- Bevel adjustment with positive stops at 22.5° and 45°
- Includes: Guide rule, hex wrench, carbide tipped black M-Force saw blade

Model No. TLV574
Mfg. No. 500FA
Price/Each \$

SPECIFICATIONS

Amperage:	15.0
No Load RPM:	5800
Depth of Cut at 45°:	1 3/4" (1 3/8" at 50°)
Depth of Cut at 90°:	2 1/2"
Tool Weight:	11.1 lbs.



7 1/4" CIRCULAR SAWS

- Heavy-duty aluminum base plate for jobsite durability
- Well balanced design for better control from above or behind the saw
- Bevel capacity of 45°
- Includes: 1 ea. 7-1/4" Blade 24T, Wrench 13 (782016-4)

Model No. TF382
Mfg. No. 5007NB
Price/Each \$

SPECIFICATIONS

Amperage:	15.0
No Load RPM:	5800
Depth of Cut at 45°:	1 3/4"
Depth of Cut at 90°:	2 3/8"
Tool Weight:	11.2 lbs.



7 1/4" LEFT BLADE CIRCULAR SAWS

- Handle position can be moved to eight different positions
- Full 50° bevel capacity
- Cut visibility for right hand users with the blade on the left side
- Includes: Case, blade and hex blade wrench

Model No. TEA172
Mfg. No. 6391-21
Price/Each \$

SPECIFICATIONS

Amperage:	15.0
No Load RPM:	5800
Depth of Cut at 45°:	1 13/16"
Depth of Cut at 90°:	2 7/16"
Tool Weight:	10.4 lbs.



TILT-LOK™ 7 1/4" CIRCULAR SAWS

- Handle can be moved to different positions
- Full 50° bevel capacity
- Quick-Lok™ cord
- Includes: Blade and hex blade wrench

Model No. TEA173
Mfg. No. 6394-21
Price/Each \$

SPECIFICATIONS

Amperage:	15.0
No Load RPM:	5800
Depth of Cut at 45°:	1 13/16"
Depth of Cut at 90°:	2 7/16"
Tool Weight:	10.4 lbs.



8" METAL CUTTING SAWS

- Durable blade shield with integral chiptank deflects hot chips and sparks
- Quick-release shield latch for fast waste disposal and blade changes
- Lever's location ensures user has both hands firmly on the saw
- Includes: Case, circular saw blade and hex blade wrench

Model No. TEX280
Mfg. No. 6370-21
Price/Each \$

SPECIFICATIONS

Amperage:	13.0
No Load RPM:	3700
Depth of Cut at 90°:	2 9/16"
Tool Weight:	13.3 lbs.



8 1/4" CIRCULAR SAWS

- High performance magnesium blade casing and base
- Bevel adjustment with positive stops at 22.5°, 45°, and 50°
- Electric brake, two built in LED lights, rubberized grips
- Includes: Carbide tipped blade, guide rule, hex wrench

Model No. TLY363
Mfg. No. 5008MGA
Price/Each \$

SPECIFICATIONS

Amperage:	15.0
No Load RPM:	5200
Depth of Cut at 45°:	2 1/4" (2" at 50°)
Depth of Cut at 90°:	3
Tool Weight:	11.2 lbs.

