

TORQUE WRENCHES



TORCOFIX TORQUE WRENCHES

- Robust torque wrench with square drive and integrated ratchet head function for controlled bi-directional tightening
- Serial number on the wrench and the provided certificate allow for unambiguous product identification
- Mushroom head prevents an unintentional pulling out of the whole square drive when changing the nut socket
- Locking button enables reliable locking of the torque setting
- Ergonomically shaped, black plastic handgrip with calibration aid
- Micrometre scale for main N.m scale for setting interim values
- Dual scale N.m and ft-lbs. below a window with a magnifying glass effect
- Release system triggers a tactile and audible signal
- Guaranteed precision of $\pm 3\%$ on the scale set torque



GEDORE

Model No.	Mfg. No.	Overall Length"	Drive Type	Torque Range	Increments	Price /Each
UAG329	2201429	8-3/4	1/4" Square	0.75 - 3.7 lbf. Ft, 1 - 5 N.m	0.25 Nm, 0.25 ft-lbs.	
UAG330	1545132	11-1/4	1/4" Square	3.7 - 18 lbf. Ft, 5 - 25 N.m	1 Nm, 1 ft-lbs.	
UAG331	1545140	13	1/4" Square	10 - 50 N.m, 7.5 - 37 lbf. Ft	2.5 Nm, 2.5 ft-lbs.	
UAG337	7674330	27	3/4" Square	60 - 300 lbf. Ft, 80 - 400 N.m	10 Nm, 10 ft-lbs.	
UAG338	7674760	37-1/2	3/4" Square	110 - 550 N.m, 80 - 405 lbf. Ft	10 Nm, 10 ft-lbs.	
UAG339	1521365	48-1/2	3/4" Square	110 - 550 lbf. Ft, 150 - 750 N.m	10 Nm, 10 ft-lbs.	



REPLACEMENT MUSHROOM HEAD DRIVES

Model No.	Mfg. No.	Drive Connector Square (Female)	Drive Connector Square (Male)	Price /Each
UAG332	1545167	3/8" (10 mm)	1/4" (6.3 mm)	
UAG333	1566385	3/8" (10 mm)	3/8" (10 mm)	
UAG341	7079370	1/2" (12.5 mm)	1/2" (12.5 mm)	
UAG342	7079450	1/2" (12.5 mm)	3/8" (10 mm)	

DREMOMETER TORQUE WRENCHES

- Precision torque wrench for lots of different applications
- Long service life even when subjected to extreme continuous use
- Excellent design for safe, fault-free use
- Easy, user-friendly torque adjustment for reliable working
- Non-losable hexagon key in the handgrip
- Strong, high-strength yet light, long-lasting aluminium alloy
- All dremometer models come with a test certificate to DIN EN ISO 6789:2003.
- Two scales on each dremometer indicate N.m and the common US unit of torque measurement
- Guaranteed precision of $\pm 3\%$ on the scale set torque



UAG451

GEDORE

Model No.	Mfg. No.	Overall Drive Length"	Drive Type	Torque Range	Increments	Price /Each
UAF442	777544010-35/64	1/4"	Square	6 - 30, 50 - 270 in-lbs.	1 N.m/10 in-lbs.	
UAF445	768200013-5/16	3/8"	Square	8 - 40, 70 - 350 in-lbs.	5 N.m/50 in-lbs.	
UAF449	768332018-3/16	1/2"	Square	25 - 120, 18 - 90 ft-lbs	5 N.m/5 in-lbs.	
UAF451	768553021-11/16	1/2"	Square	40 - 200, 30 - 150 ft-lbs	5 N.m/5 in-lbs.	
UAF456	768545024-19/64	1/2"	Square	60 - 300, 45 - 220 ft-lbs	5 N.m/5 in-lbs.	
UAF460	768847028-15/64	3/4"	Square	80 - 360, 60 - 260 ft-lbs	5 N.m/5 in-lbs.	
UAF464	142715631-31/32	3/4"	Square	110 - 550, 80 - 400 ft-lb	10 N.m/10 in-lbs.	
UAF467	769150031-31/32	3/4"	Square	155 - 760, 115 - 560 ft-lbs	10 N.m/10 in-lbs.	
UAF473*	767018031-31/32	3/4"	Square	155 - 760, 115 - 560 ft-lbs	10 N.m/10 in-lbs.	
UAF477*	769401031-31/32	3/4"	Square	520 - 1000, 380 - 730 ft-lbs	10 N.m/10 in-lbs.	

* Includes: (1) ALU extension tube (762 mm)

M12 FUEL™ DIGITAL TORQUE WRENCH KITS

- PowerState™ brushless motor
- One-Key™ technology allows for customization, tracking, tool security, and inventory management
- Adjustable run-down torque to control the tool's output torque via the motor to prevent over torque
- RedLink Plus™ Intelligence enables advanced communication between batteries and tools
- Four notification modes that the tool is reaching, meeting or exceeding the torque target (audible, LED, LCD, and vibratory)
- Six pre-programmed languages including English, Spanish and French
- Durable design to withstand the most demanding jobsite environments
- Includes: (2) M12™ Redlithium™ CP2.0 battery packs, (1) M12™ Lithium-ion battery charger, (1) Carrying case, (1) Calibration certificate
- Voltage: 12 V
- Tool Accuracy: CW
- Ratcheting Angle: 4.5°
- RPM: 0 - 100
- Measuring Units: ft-lbs, in-lbs., N.m, kg-cm



UAI587

Milwaukee

Model No.	Mfg. No.	Anvil Size Ball Detent"	Torque Range	Length"	Price /Each
UAI587	2465-22	3/8	10 - 100 ft-lbs.	23.3	
UAI588	2466-22	1/2	12.5 - 150 ft-lbs.	23.5	

INDUSTRIAL BREAKING TORQUE WRENCHES

- Robust, all steel construction with corrosion-resistant finish is ideal for the automotive, bus and truck, chemical, energy and nuclear industries, as well as major construction and engineering projects
- Adjustability is provided by calibrated scales that allow the user to adjust the tool to their desired torque setting, enabling a range of different torque settings to be applied
- A visible micrometer style scale allows the user to adjust the tool quickly and easily to their desired torque setting
- Breaking mechanism reduces the risk of incorrect tightening
- Dual scales (N.m and lbf.ft)
- Supplied with an ISO 6789 calibration certificate and storage case



UAF439

GEDORE

Model No.	Mfg. No.	Overall Length"	Drive Type	Torque Range	Repeatability	Price /Each
UAF438	3022854	44	3/4" Square	100 - 500 lbf. Ft, 150 - 700 N.m	+/- 4%	
UAF439	3022862	43-7/8	3/4" Square	150 - 600 lbf. Ft, 200 - 800 N.m	+/- 4%	
UAF440	3022870	54	3/4" Square	200 - 750 lbf. Ft, 300 - 1000 N.m	+/- 4%	