

TAPES & ADHESIVES

DOUBLE-SIDED POLYESTER FILM TAPE

- Ideal for general mounting and holding
- Polyester film coated on both sides with a high shear strength adhesive; silicone paper liner
- Ideal for carpet laying, trophies, mouldings and picture frames
- Bonds to paper, foil and plastic film
- 180' (55 m) per roll
- Thickness: 6.5 mils



Priced per Roll

| Model No. | Width | Rolls/Case | Price/Each |
|-----------|------------|------------|------------|
| PE826 | 24 mm (1") | 48 | |
| PE827 | 48 mm (2") | 24 | |

DOUBLE-SIDED PAPER TAPE

- Made of thin kraft and rope fibre tissue, coated on both sides with an aggressive high shear strength adhesive; silicone paper liner
- Features include thinness and ease of application
- 108' (33 m) per roll
- Thickness: 5 mils



Priced per Roll

| Model No. | Width | Rolls/Case | Price/Each |
|-----------|--------------|------------|------------|
| PA677 | 12 mm (1/2") | 72 | |
| PA678 | 24 mm (1") | 36 | |
| PA679 | 48 mm (2") | 24 | |

VINYL TAPE 471

- Ideal for many colour coding, abrasion protection, sealing, patching, splicing, wrapping and general purpose applications
- For use around fire extinguishers, electrical equipment
- 33 m (36 yards) per roll




Priced per Roll

| Model No. | Width | Colour | Rolls/Case | Price/Each |
|-----------|--------------|--------|------------|------------|
| PC589 | 1/2" (12 mm) | Red | 72 | |
| PC590 | 1/2" (12 mm) | Blue | 72 | |
| PC591 | 1/2" (12 mm) | Yellow | 72 | |
| PC592 | 1/2" (12 mm) | White | 72 | |
| AMC510 | 3/4" (18 mm) | Red | 48 | |
| AMC461 | 3/4" (18 mm) | Blue | 48 | |
| AMC547 | 3/4" (18 mm) | Yellow | 48 | |
| AMC533 | 3/4" (18 mm) | White | 48 | |

DOUBLE COATED POLYETHYLENE FOAM TAPE 4466

- 1/16", thick closed cell polyethylene foam carrier
- High tack rubber adhesive
- 3.0-mils, densified kraft liner
- Temperature and environmental resistant
- Colour: White



Priced per Roll

| Model No. | Dimensions | Rolls/Case | Price/Each |
|-----------|----------------|------------|------------|
| PB921 | 1/2" x 36 yds. | 18 | |



SCOTCH® ATG ADHESIVE APPLICATORS

- Pressure sensitive two-way adhesive can be applied exactly where needed
- Ideal for mounting, splicing or bonding
- Can be used in a broad range of industries, including printing, furniture manufacturing, electronics, appliances, signs and displays, automotive and others
- ATC system applies 2-mils reinforced clear acrylic adhesive and simultaneously rewinds the tape liner inside the dispenser



Priced per Roll

Model No. PA974
Mfg. No. ATG-700
Price/Each \$

TAPE

| Model No. | Mfg. No. | Description | Rolls/Case | Price/Each |
|-----------|----------|------------------|------------|------------|
| PA612 | 924-12 | 1/2" x 108' Tape | 72 | |
| PA613 | 924-19 | 3/4" x 108' Tape | 48 | |

TEFLON TAPE

- Provides fast positive seal for water lines, sewage, and sprinkler systems
- Effective on metal or plastic threads
- 3-mils thick, density 1.35-1.50 grams/cubic centimetre
- Complies with MIL-T-27730A



Priced per Roll

| Model No. | Dimensions" | Colour | Rolls/Case | Price/Each |
|-----------|-------------|--------|------------|------------|
| PD095 | 1/2 x 260 | Pink | 50 | |

TEFLON THREAD SEALANT TAPE

- For use in sealing threaded pipe joints
- Non-toxic composition suitable for solvents, chemicals, oxygen and on food lines
- Permits easy disassembly even after years of service
- Works under pressures up to 10 000 PSI and temperatures from -450°F to 550°F



Priced per Roll



| Model No. | Dimensions" | Rolls/Case | Price/Each |
|-----------|-------------|------------|------------|
| PA684 | 1/2 x 520 | 144 | |
| PA685 | 3/4 x 520 | 144 | |

TEFLON SEALING TAPE

- Commonly used in plumbing for sealing pipe threads
- Ensures a tight seal
- Works for both water and air
- Colour: White
- Tape Material: PTFE
- Thickness: 3 mils (0.0762mm)
- Density: 0.37 grams/cubic centimeter
- Working Temperatures Range: -190°C to 260°C (-310°F to 500°F)



| Model No. | Dimensions | Price/Each |
|-----------|------------|------------|
| PG148 | 1/2 x 520 | |
| PG149 | 3/4 x 520 | |