

LPS 3® HEAVY-DUTY INHIBITORS

- Protects up to two years
- Stops rust and corrosion
- Provides non-sling lubrication
- Non-flammable propellant
- Self-healing, waxy film
- Provides anti-seize coating
- Safe to use on rubber, fabric, plastics and paints
- Meets or exceeds these specs: Boeing BMS-3 23F Type II, MIL-C-0083933A, para.3.2-3.16, MIL-C-16173D Grade 2 Class I, DMS 2150, Airbus TN A. 007.10138 Type I Grade 2
- Accepted for use in Canadian food processing facilities



Model No.	Mfg. No.	Size	Price /Each
AA808	C00316	11 oz.	
AB559	C00322	20-oz. trigger	
AB558	C03128	1 gal.	
AB556	C00305	5 gal.	
AB557	C00355	55 gal.	

TKX ALL-PURPOSE LUBRICANT

- Non-flammable CO₂ propellant
- Displaces moisture
- High flash point of 175°F (79°C)
- Protects against corrosion
- Loosens rusted or frozen parts
- Does not contain chlorinated solvents or silicones
- Safe on most surfaces
- Inverts spray valve lets you spray in all directions
- NSF registered category code H2
- Provides non-drying long-lasting, oily film



Model No.	Mfg. No.	Size	Price /Each
AA846	C02016	11 oz.	
AB490	C02028	1 gal.	
AB638	C02005	5 gal.	
AB639	C02055	55 gal.	

BRIGHT COAT COLD GALVANIZE CORROSION INHIBITORS

- Shiny zinc coating
- Prevents rust and corrosion on all metals
- Restores hot dip galvanizing
- Dries to touch in 15 to 30 minutes
- Repairs rusted, galvanized and welded surfaces
- Electrochemically protects bare metal
- Heat resistant, flexible coating
- Will not yellow, chalk, crack or peel



Model No.	Mfg. No.	Size	Price /Each
AB485	C05916	13 oz.	

LST PENETRANT

- Specially formulated with low surface tension for fast penetrating action
- Attacks rust and corrosion to free frozen parts
- Powerful foaming action provides complete surface coverage
- Displaces moisture
- Lubricates and protects metal surfaces
- Flash point of 175°F (79°C)
- Inverts spray valve lets you spray in all directions
- NSF registered category code H2



Model No.	Mfg. No.	Size	Price /Each
AA843	C01916	11 oz.	

PENETRATING OIL

- Flashpoint: 60.6°C
- Slow evaporation rate
- A no-compromise penetrant that attacks corrosion to free corroded fasteners and mechanical components
- A super-fast, powerful, concentrated penetrating solvent that loosens and cleans
- Instantly penetrates tightly fitted crevices
- NSF Registered H2



Model No.	Mfg. No.	Size	Price /Each
YB991	73060	312 g	

KB 88 THE ULTIMATE PENETRANT


- Quickly releases rusted and corroded nuts, bolts, hinges and other frozen components
- Extremely high solvency, low surface tension
- Enhanced penetration and lubrication
- Outperforms the competition in independent lab tests
- Penetrates faster and deeper than most other similar products in the market place
- Inverts spray valve
- NSF registered category code H2
- VOC compliant



Model No.	Mfg. No.	Size	Price /Each
AD970	C02316	13 oz.	
AD297	C02322	20 oz. trigger	

WD-40

- Loosens rusted parts
- Displaces moisture
- Non-conductor, dries out electrical and electronic equipment
- Stops squeaks
- Lubricates and protects against moisture and corrosion
- Operating temperature: -50°F to 300°F
- Minimum flash point 110°F open cup



Model No.	Mfg. No.	Size	Price /Each
NA610	1005	155 g aerosol	
NA611	01111	11 oz. aerosol	
NA609	01010	3.785 L	

BOLT-OUT™

- Penetrates then lubricates
- Faster disassembly with less effort
- Inhibits further rust
- Displaces moisture
- No chlorinated solvents
- Non-flammable liquid formula
- Effective at wide temperature range



Model No.	Mfg. No.	Size	Price /Each
YC429	53-D 892	400 ml	
AC310	53-D 893	500 ml trigger	
AA479	53-D 897	20 L	
AC311	53-D 898	200 L	

SCREWLOOSE™ SUPER PENETRANT

- Maximum Working Temperature: 141°F (61°C)
- Ideal for rusted and frozen metals
- Can also be used as a multi-purpose lubricant



Model No.	Mfg. No.	Size	Price /Each
AF244	75330	312 g	